



Kobelt's SMS Communications Module provides support for broadcasting of system status over SMS messaging from anywhere there is an active cellular network connection. It connects directly to the Vitals System Display Panel. Management and configuration of messages are handled directly through the Vitals System Display Panel.

Specifications

- Operating Voltage: 12 VDC and 24 VDC
- Maximum Current: < 500 mA
- Interface: RS-422
- Cellular Antenna: External
- IP Rating: IP42
- Operating Temperature: -20°C to 55°C [-4°F to 131°F]
- Product Weight: 0.2 kg [0.44 lbs]

Key Benefits

- Monitors and reports status over SMS messaging
- SIM card pre-installed
- Standard cellular antenna included
- Designed for use with Vitals System
- Easy and intuitive installation and setup

EXTERNAL ANTENNA OPTION



External antenna for 2G wireless (3 metre cable) - VT321

STANDARD ORDERING INFORMATION

KOBELT P/N	MODEL #	PRODUCT DESCRIPTION
6700-0320	VT320	SMS COMMUNICATIONS MODULE FOR VITALS SYSTEM
6700-0321	VT321	EXTERNAL ANTENNA FOR 2G WIRELESS (3 METRE CABLE)
6700-0322	VT322	STANDARD STUB ANTENNA FOR 2G WIRELESS (FOR REPLACEMENTS)